

## CONTENTS

- Vekshin M. M., Hotnyanskaya E. B., Nikitin V. A., Yacovenko N. A. Integrated-Optic Polarization Refractometer . . . . . 3**

A high-sensitive polarimetric-type micro-waveguide refractometer is proposed. It is based on four-layer optical waveguide structure with dielectric isotropic layers, having significant modal birefringence, as a transducer element working. Phase shift of orthogonally polarized guided waves has linear dependence on index of cladding medium. The sensitivity is of an order  $1 \cdot 10^{-6}$ .

- Korolev M. A., Chaplygin Iu. A., Tohonov R. D. The Integrated Microsystems — a New Generation By the Element Base . . . . . 6**

The integrated microsystem is represented a smart power switch. At is show, that the use of CMOS technology is to be made the power switch microsystem.

- Nikolski K. N., Baturin A. S., Kupryashkin A. S., Tchesov R. G., Sheshin E. P. "Ring Effect" in High Current Field Emission . . . . . 8**

The effect of ring appearance in the flat vacuum diode is described. During the tests of flat cathodes produced by electrophoresis, electrochemical deposition or by CVD methods we observed one, two and sometimes three rings appear in high current mode. The model of rings appearance is given. It is shown, that rings formed by electrons scattered from the anode. Ring size independent at applied voltage and cathode current. It is determined by anode-cathode distance for flat diode. Diameter of ring is 4 times greater than anode-cathode distance. Results of experimental confirmation of the proposed model are presented. The possibility of the "ring effect" application is discussed.

- Mikhailov P. G. Formgenerator Processes of the Creation of Micromechanical Devices . . . . . 10**

Available techniques for patterning structures for microelectronic sensors are analyzed. Methodology for MEMS patterns analysis based on anisotropy of source material and etchant properties is proposed.

- Glushanin S. V., Topolov V. Yu. An Analysis of electromechanical Properties of 1—2 composites based on poled ferroelectric ceramic . . . . . 13**

An algorithm for determination of effective elastic, piezoelectric and dielectric constants has been proposed within the framework of a new model of the 1—2 composite "poled ferroelectric ceramic — polymer". An effect of zigzag-like ferroelectric ceramic inclusions on non-monotonic and reversal-of-sign behaviour of different types of piezoelectric coefficients has been analysed. It has been shown that such behaviour has no analogs among the known two-component composites.

- Gaikovich K. P., Dryakhlushin V. F., Zhilin A. V. The Improvement of the Resolution of SNOM-Images Taking into Account the Probe Transfer Function . . . . . 19**

Significant enhancement of resolution in the scanning near-field optical microscopy (SNOM) is achieved by deconvolution of measured 2-D distributions using Tikhonov's method taking into account the probe transfer function that was determined by smallest details of a processed image.

- Kaljaev I. A. Purposedistribution Algorithm in "Cloud" of Microrobots . . . . . 21**

The problem of decomposition of the "cloud" of microrobots into groups (clusters) intended for decision of the goal problems set posed before the "cloud" is considered. Clusterization algorithm of the "cloud" based on the strategy of the collective taking up the decisions and differing the simple technical realization is suggested. The results of the experimental researches of the developed algorithm on the programmed model are reduced.

- Ageev O. A., Svetlichnyi A. M., Kocherov A. N. Optimization of Temperature and Thermoelastic Stress in SiC Wafer under Rapid Thermal Infrared Heating . . . . . 25**

In this paper we have investigated the dependence of heater construction on distribution of exposure, temperature, radial and tangential stress elements, criterion of defect formation by the radius of 100 mm diameter SiC wafer under rapid infra red heating. Defined the optimal heating conditions, which not lead to linear defects formation.

- Adamatzky A., De Lacy Costello B., Melhuish K., Ratcliffe N., Wessnitzer Ya., Rambidi N. G. Controlling Autonomous Mobile Robots based on Chemical Belousov—Zhabotinsky Type Media . . . 29**

Basic principles and some results of investigations on experimental chemical controllers for autonomous mobile robots are discussed. General features of spatio-temporal dynamics of chemical reaction-diffusion media were used when designing model devices, namely spreading wave excitations, and specific wave interactions. Offered prototypes of chemical controllers uses information processing by reaction-diffusion media, simplicity of information input and output, and robustness of computational process resulting from large-scale parallelism of medium architecture, that is because of a multitude of computing primitives (micro-volumes) of the medium functioning in a parallel model. Examples of chemical controllers for robot navigation, finding the shortest paths in a complicated neighborhood, and image processing are under consideration.

- Usanov D. A., Skripal A. V. Characteristic Vibration Determination of Microobjects by Laser Radiation . . . . . 34**

The measurement results of characteristic vibrating microobjects by methods of holographic and speckle interferometry and homodyne and autodyne interferometry are presented. The possibility of registration of nonhomogeneous objects, complicated periodical movements, as well as vibrations of detached biological organs are shown. The determination possibility of nano-meter vibrations by wideband autodyne system based on semiconductor laser are investigated.

- Landyshev A. V., Bitiutskaya L. V., Kosakov A. T. Research of Alloy Surface (Bi; Sb)<sub>2</sub>Te<sub>3</sub> with Electron-Probe Methods . . . . . 42**

Alloy surface based on Bi—Sb—Te was investigated with the Auger-electron spectroscopy and Electron-microscope analysis. It was found out, that industrial carbon concentration depends on the preferred orientation of alloy crystalline grains.

Carbon saturates such surface more intensively, which are parallel to a pressing effort.

## Подписку за рубежом принимают:

For foreign subscribers:  
ЗАО МК-Периодика. E-mail: info@periodicals.ru;

Editor-in-Chief Ph. D. Petr P. Maltsev  
Index 79493.

Address is: 4, Stromynsky Lane, Moscow, 107076, Russia. Tel./Fax: (7 095) 269-5510.