

CONTENTS

Teletc V. A. Microelectromechanical Inertial Transducers of Physical Quantities: Typical Design Variants 2

The microelectromechanical accelerometers are the leaders of sales of inertial microelectromechanical systems (MEMS) due to automobile electronics development. However the inertial MEMS-devices market keeps spreading by the high sensitive micro-seismosensors and gyroscopes. Most widely used designs of them are briefly overviewed.

Luchko V. A. MEMS-technology Changed Notion about Technology of Infrared Vision. 6

In this article the matrix receiver of infrared vision consisted of thousand photosensitive microconsoles on a basis of SiC are described.

Kozlov A. G. Modelling of Steady-State Temperature Distribution in Gas Microsensors Based on Thermally Isolated Structures 8

An analytical method is presented that allows one to determine the steady-state temperature distribution in gas microsensors based on thermally isolated structures made with an anisotropic etching of silicon. The structure of a microsensor is divided into a number of two-dimensional rectangular regions in which the temperature distribution is obtained by means of Fourier method. Parameters characterising thermal conduction processes between adjacent regions are found using adjoint boundary conditions. As an example, the temperature distribution in two structural variants of catalytic gas sensor on the thermally isolated structures is determined.

Balan N. N. Definition of Mems-Structures Elastic Properties 14

It is described a finite element method of multilayered plates modeling, offered to use at modeling of elements of MEMS-structures. On an example of a tunnel sensor membrane simulation and comparison of the received results with analytical calculation efficiency of application of the offered method is shown. Lacks of a method and ways of their elimination are discussed.

Usanov D. A., Skripal A. V., Kamyshanckiy A. S. Velocity Measurement of Object Movement by the Spectrum of Autodyne Signal of Semiconductor Laser on Dimensional Quantum Structures 19

The application possibility of laser autodyne on dimensional quantum structures for velocity measurements of nanometer displacements has been researched. Additional mechanical vibrations with amplitude no less than half of wavelength of laser radiation were excited in an object to provide autodyne signal normalization. In this case the displacement velocity were determined by phase changing of autodyne signal.

Todua P. A., Bykov V. A., Volk Ch. P., Gornev E. S., Zhelkobaev Zh. etc. Scientific and Technological Bases of Metrological Security of Length Dimension in Micrometer and Nanometer Ranges and their Intrusion in Microelectronics and Nanotech-nologies 24

The bases of metrological security of the dimensions based on the methods of scanner probe microscopy and laser interferometer — phasemeter are represented. The methods and means of reproduction and transmission of the unit of length dimension in the indicated range with absolute binding to the state primary standard of the unit of length — the meter are offered; the technology is developed and tree-dimensional micro-nanorelief of surface are created and also the algorithms and the package of programs permitting to realize the automatized tree-dimensional dimension of the condensed environments are created.

Gaikovich K. P. Mironov V. L. Reconstruction of LDOS of HOPG Surface by Data of Scanning Tunneling Microscopy 39

A sub-atomic resolution in the scanning tunneling microscopy is achieved by deconvolution of measured images taking into account the smoothing property of the probe transfer function. This method makes it possible to obtain the image of thin structure of LDOS of the HOPG lattice.

Подписку за рубежом принимают:

For foreign subscribers:
ЗАО МК-Периодика. E-mail: info@periodicals.ru;

Editor-in-Chief Ph. D. Petr P. Maltsev
Index 79493.

Address is: 4, Stromynsky Lane, Moscow, 107076, Russia. Tel./Fax: (7 095) 269-5510.