

CONTENTS

Shevchenko V. Ya., Samojlovich M. I. *Geometry, Information and Structure of Nano-Peace* 2

The generalized principles of the structural chemistry of nanosized objects are discussed. The necessity of an extended symmetry treatment is pointed out related with going over to the consideration of the special constructions of the algebraic geometry. The concept of the geometrical structural complexes is examined.

Gruzdev A. O. *The Development of Educational Nano-Laboratory on the Basis of SPM "Nanoeducator" and Apple Platform* 8

In this paper basic stages of "Nanoeducator" Scanning Probe Microscope (SPM) improvement are described. New MacOS X software development with principal problems and their solutions as well as future project development are analyzed.

Amelichev V. A., Verner V. D., Il'kov A. V., Saurov A. N. *Correlation between Micro System Technology and Technology of Microelectronics itself* 10

There are more than 20 technologies of micro treatments for using in micro systems fabrication. It is clear that for mass production of indicated above devices is Si based technology of micro treatment. Using example of formation elastic MEMS it was shown ways of its fabrication technology of CMOS integrated micro circuits. Optimal way is simultaneous fabrication of general technological layers on the base of joint manufacturing CMOS and MEMS components can be development.

Shcheglov P. A., Nikishina E. E., Drobot D. V., Lebedeva E. N. *Prospective Technology of Metallic and Oxide Nano-Materials Based on Less-Common Elements* 15

The article represents an overview of work aimed on the creation of methods of obtaining of metallic and oxide nano-materials based on less-common elements (Nb, Ta, Re, Mo, W, Rare Earths) possessing a complex of controllable properties. The underlying concept is the preparation of powders by thermal destruction of precursor phases (single- and multi-metal oxohydroxide or oxoalkoxide compounds). The suggested technology allows obtaining nano-sized powders of refractory metals and alloys, simple and complex oxides, and their solid solutions, which are promising in application in nano- and micro-technology.

Pavlov S. V. *Influence of Electric Field, Impurities and Boundary Electromechanical Stresses on Polarization Profile of thin Ferroelectric Film* 18

Influence of external electric field, impurities and electromechanical interaction with substrate material on the polarization profile of ferroelectric thin film has been theoretically studied. The obtained results are in a good agreement with experimental data of polarization profile in thin films of lead titanate-zirconate (PZT) ceramics with PbO impurity. Physical meaning of negative extrapolation length is discussed.

Shautsukov A. G., Kizilov I. M., Kuznetsov G. D. *The Modelling of Process of Formation Alloyed by Recoil Atoms of Layers* 21

There are developed the algorithms of modelling of process of formation nanodimensional layers alloyed by recoil atoms. Algorithms provide

modelling process of introduction of recoil atoms in a layer with the set parameters and modelling of process photon annealing alloyed layer by recoil atoms. Numerical experiment is carried out and are determined: parameters received alloyed by recoil atoms of layers; a degree of redistribution of the introduced recoil atoms at photon annealing the created layers.

Rembeza E. S., Svistova T. V., Rembeza S. I., Komarova A. S., Dyrda N. N. *Nanocomposites $\text{SnO}_x\text{:MnO}_y$ for Microelectronic Gas Sensors* 23

The possibility of use film nanocomposite $\text{SnO}_x\text{:MnO}_y$ as gas sensitive layers for microelectronic gas sensors is discussed. Nanocomposites on the base SnO_2 were fabricated by reactive ion-beam sputtering of composite target in the ambient of $\text{Ar} + \text{O}_2$. Element composition, electrical-physical properties and gas sensitivity of the films were studied. It is shown that Mn additive decreases temperature of maximal gas sensitivity of film nanocomposites to ethanol, acetone, ammonia, propanol and formaldehyde vapors in the air. The conclusion about perspective of using film nanocomposites $\text{SnO}_x\text{:MnO}_y$ for microelectronic gas sensors is done.

Afonin S. M., Afonin P. S. *Modelling Characteristics of Sectional Piezoactuators for Nano- and Micromanipulators* 25

Statics and dynamic characteristics of simple, sectional and composite piezoactuators for nano- and micromanipulators are proposed. Effect of geometric and physical parameters of piezoconverter and external load on its statics and dynamic characteristics are determined. Main features and principles of program-apparatus means for system modelling characteristics of simple and sectional piezoactuators are presented.

Abramov I. I., Dvornikov O. V. *The Bipolar-JFET IC Simulation Sequence in the "Spice"-like Programs* 30

The IC's schematic simulation sequence for the "Spice"-like programs is proposed. It is well-suited for employment with system approach to analog bipolar-JFET LSI/VLSI synthesis.

Tikhonov R. D. *A Dual-Collector Magnetotransistor: Negative Sensitivity, Absolute Sensitivity and Noises* 36

With the help of modern device-technological modeling the distributions of carriers of a charge, density of currents and recombination speed in two-collector lateral bipolar the magnetotransistor generated in a well at external connection of contacts to a substrate and to a well are investigated. The experimental research dual-collector lateral bipolar magnetotransistor with base in well, as sensor of weak magnetic fields is spent. The absolute sensitivity 900 V/T, voltage of noise in a working mode and resolution $5 \cdot 10^{-10}$ T is determined.

Godovitsyn I. V. *Calculation of Curvature of Electrostatically Deflected MEMS RF Switches by Analytical and Finite-Element Approaches* 41

In this work 2D calculation of deformation of electrostatically deflected MEMS RF switches using energy minimization method (Ritz method) is performed. Alternatively simulation of the same structures with help of finite-element implemented software (ANSYS) is carried out. Good agreement of results provided by both methods is shown and applicability of faster Ritz method to calculation of curvature of electrostatically controlled MEMS RF switches is discussed.

For foreign subscribers:

Journal of "NANO and MICROSYSTEMS TECHNIQUES" (Nano- i mikrosistemnaa tehnika, ISSN 1813-8586)
Joint-stock company MK-Periodica. E-mail: info@periodicals.ru Tel.: +7(495) 684-5008. Fax: +7(495) 681-3798

The journal bought since november 1999.

Editor-in-Chief Ph. D. Petr P. Maltsev

ISSN 1813-8586.

Address is: 4, Stromynsky Lane, Moscow, 107076, Russia. Tel./Fax: +7(495) 269-5510.

E-mail: nmst@zknet.ru; <http://www.microsystems.ru>

Адрес редакции журнала: 107076, Москва, Стромынский пер., 4/1. Телефон редакции журнала (495) 269-5510. E-mail: nmst@zknet.ru

Журнал зарегистрирован в Федеральной службе по надзору за соблюдением законодательства в сфере массовых коммуникаций и охране культурного наследия.
Свидетельство о регистрации ПИ № 77-18289 от 06.09.04.

Дизайнер Т. Н. Погорелова. Технический редактор И. С. Павлова. Корректор Е. В. Комиссарова

Сдано в набор 01.09.2006. Подписано в печать 04.10.2006. Формат 60×88 1/8. Бумага офсетная. Печать офсетная.

Усл. печ. л. 6,86. Уч.-изд. л. 8,94. Заказ 1627. Цена договорная

Отпечатано в Подольской типографии — филиал ОАО "ЧПК", 142110, г. Подольск, ул. Кирова, 15